

The all new Airtocheck negative pressure monitor.



www.airtocheck.com



Full color touchscreen with 2 or 4 channels.



New design based on innovation and feedback from Airtocheck users.

- Unique new technique! Web-based monitor remotely adjustable from your desk or via phone/tablet.*
- A high-end monitor for the competitive price you are used to from us.
- Easy to operate full color touchscreen!
- Directly readable SD card.
- New printer for longer printing on 1 roll.
- Adjustable print interval.
- Available with 2 or 4 channels.
- Each channel equipped with relay block connection.
- Even more resistant to dust and moisture due to modified design.
- Lighter and more impact resistant.
- Longer 8 mm hose available.

The new monitor comes with a new website*

- New design with dashboard and even faster exports to PDF.
- Negative pressure monitor remotely adjustable via website via PC, laptop, phone and tablet.
- Connection with third party software possible.

For more information, please contact your local dealer.



Technical specifications:		
Version	RM-402T / RM-404T	
Size	$33.5 \text{ cm } \times 29 \text{ cm } \times 14.5 \text{ cm}$	
Weight	3,0 kg	
Power	100-240V AC 50/60Hz 25W	
Battery	7 hours (max.**)	
Temperature	Effective 0-40 gr Celsius	
Pressure range	-40 / +1 Pa	
Display	4,3" TFT Touchscreen	
Relay connection	Each channel	
Memory	4 days (max.***)	
SMS	Yes (SIM card required)	
Internet	Optional	
SD kaart	Yes	
Channels	2 (RM-402T), 4 (RM-404T)	
Case	Splash-proof, impact-resistant	
Printer	Thermisch	
Connections	External horn	
	External relay block	
Included	Manual, 8mm hose (3 meter),	
	SD card and power adapter	

* GO-live planned Q4 2021

** Depending on usage of the number of channels and accessories.

*** Depending on the number of channels used.

Prices:		
2 channels	Standard	€ 1.100,00
4 channels	Standard	€ 1.400,00
2 channels	Web-based	€ 1.350,00
4 channels	Web-based	€ 1.550,00